

Specifications

C

Table C-1 *Routermate 56/64 CSU/DSU Specifications*

ITEM	SPECIFICATION
Operating Modes	DDS and Limited Distance Line Driver (point-to-point)
Network Interface Rate Format Termination	56 kbps and 64 kbps clear channel Bipolar, Return-to Zero 8-position, RJ48S
Synchronous Data Port Rate Termination	56 kbps and 64 kbps CCITT V.35, 34-pin female (DCE)
Console Interface Rate Termination	9600 bps, 8+N+1 RS-232, 25-pin female
SNMP Interface Rate Termination	Configured for SLIP and async telnet 9600 bps 8-position, RJ48S
Modem (optional) Format Termination	Asynchronous, 9600 bps, V.32 analog dial-up 6-position, RJ11
Timing	56 kbps: Internal, External, Repeater 64 kbps: Repeater
LED Indicators	DSR, RTS, CTS, DCD, TXD, RXD, TST, NIS
Power Standalone Rack	120 VAC $\pm 10\%$, 57 to 63 Hz, 5 watts 120 VAC $\pm 10\%$, 57 to 63 Hz, or -40 to -60 VDC (-48 VDC nominal) @4 amp max.

Specifications

ITEM	SPECIFICATION
Weight	
Standalone	2 pounds
Rack	1.1 pounds
Temperature	
Operating	32° to 122° F, 0° to 50° C
Storage	-40° to 158° F, -40° to 70° C
Relative Humidity	0% to 95%, non-condensing
UL Compliance	Meets UL 1459 requirements